SAFETY DATA SHEET Chemodex Limited - Chemwax 500ml Aerosols

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Chemodex Limited - Chemwax 500ml Aerosols

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Protectant

1.3. Details of the supplier of the safety data sheet

Supplier Chemodex Limited

Canal Road Worksop Nottinghamshire S80 2EH 01909 473301

1.4. Emergency telephone number

Emergency telephone +44 (0) 1909 473 301 (Hours 09:00 - 17:00 Mon to Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 1 - H222, H229

Health hazards Not Classified

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or F+; R12. R52/53

1999/45/EC)

Human health Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional

information on health hazards.

Environmental The product contains a substance which is harmful to aquatic organisms.

Physicochemical Containers can burst violently or explode when heated, due to excessive pressure build-up.

The product is extremely flammable. Vapours may form explosive mixtures with air.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated H412 Harmful to aquatic life with long lasting effects.

Chemodex Limited - Chemwax 500ml Aerosols

Precautionary statements P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapour/spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Supplementary precautionary

P273 Avoid release to the environment.

statements P501 Dispose of contents/container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM GASES, LIQUEFIED

30-60%

Classification

Flam. Gas 1 - H220

Press. Gas, Compressed - H280

HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES,

10-30%

CYCLICS, AROMATICS (2-25%)

CAS number: 64742-82-1 EC number: 919-446-0

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

10-30%

Classification

Asp. Tox. 1 - H304

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. If in doubt, get medical attention promptly.

Ingestion Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for

breathing. Get medical attention.

Chemodex Limited - Chemwax 500ml Aerosols

Skin contact Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur

after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of

water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms

occur after washing.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during

firefighting

Use water to keep fire exposed containers cool and disperse vapours. Cool containers

exposed to heat with water spray and remove them from the fire area if it can be done without

risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory

protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near

spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into

containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. See Section 12 for additional information on ecological hazards. For waste disposal,

see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's

recommendations. When sprayed on a naked flame or any incandescent material the aerosol

vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

Advice on general occupational hygiene

Wash promptly with soap and water if skin becomes contaminated.

Chemodex Limited - Chemwax 500ml Aerosols

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks

and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible.

Hand protection No specific hand protection recommended.

Other skin and body Wear suitable protective equipment for protective equipment equipm

protection

Wear suitable protective equipment for prolonged exposure and/or high concentrations of

vapours, spray or mist.

Respiratory protection No specific recommendations. If ventilation is inadequate, suitable respiratory protection must

be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Brownish.

Odour Solvent.

Odour threshold No information available.

pH No information available.

Melting point No information available.

Initial boiling point and range -41 (-41 TO 210)°C @

Flash point -40°C CC (Closed cup).

Evaporation rate No information available.

Evaporation factor No information available.

Flammability (solid, gas) No information available.

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 0.6 % Upper flammable/explosive limit: 9.5 %

Vapour pressureNo information available.Vapour densityNo information available.

Relative density 0.68

Chemodex Limited - Chemwax 500ml Aerosols

Solubility(ies) Insoluble in water.

Partition coefficient No information available.

Auto-ignition temperature 225°C

Decomposition TemperatureNo information available.ViscosityNo information available.Oxidising propertiesNo information available.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

ReactivityNo test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability The product may not be stable under some conditions of storage or use.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

None known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high

temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None at ambient temperatures.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness

and nausea.

Skin contact No significant hazard at normal ambient temperatures.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health

hazards

No known chronic or acute health risks.

Route of entry Inhalation Skin and/or eye contact

Toxicological information on ingredients.

HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

Acute toxicity - oral

Chemodex Limited - Chemwax 500ml Aerosols

Acute toxicity oral (LD50

mg/kg)

15,001.0

Species Rat

ATE oral (mg/kg) 15,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 3,401.0

mg/kg)

13,101.0

Species Rat

ATE dermal (mg/kg) 3,401.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ vapours mg/l)

Species Rat

ATE inhalation (vapours

mg/l)

13,101.0

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

Acute toxicity - oral

Acute toxicity oral (LD₅o

5,001.0

Rat **Species**

ATE oral (mg/kg) 5.001.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,001.0

mg/kg)

Species

mg/kg)

Rabbit

ATE dermal (mg/kg) 2,001.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ vapours mg/l)

5.29

Species Rat

SECTION 12: Ecological Information

12.1. Toxicity

Ecological information on ingredients.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

Acute toxicity - fish LOEC, : >100 mg/l, Fish

Chemodex Limited - Chemwax 500ml Aerosols

Acute toxicity - aquatic

plants

LOEC, : >100 mg/l, Algae

Acute toxicity - microorganisms

LOEC, : >100 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No data available

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methods Containers should be thoroughly emptied before disposal because of the risk of an explosion.

Do not pierce or burn, even after use.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

AEROSOLS

(ADR/RID)

Proper shipping name

AEROSOLS

(IMDG)

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

Chemodex Limited - Chemwax 500ml Aerosols

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended)

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 05/06/2015

Revision 1

SDS number 5676

Chemodex Limited - Chemwax 500ml Aerosols

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H226 Flammable liquid and vapour.

H229 Pressurised container: may burst if heated

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.