

Version	Revision Date:	MSDS Number:	Date of last issue: 14.01.2015
1.3	11.02.2015	33157-00004	Date of first issue: 02.12.2014

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier				
Tra	ade name	:	PURELL® Skin Nourishing Foam Hand Sanitiser	
1.2 Rele	evant identified uses of the	e s	ubstance or mixture and uses advised against	
•••	e of the Sub- ince/Mixture	:	Hand Sanitizer	
-	commended restrictions use	:	This is a personal care or cosmetic product that is safe for consumers and other users under normal and reasonably foreseeable use. Cosmetics and consumer products, specifi- cally defined by regulations around the world, are exempt from the requirement of an SDS for the consumer. While this mate- rial is not considered hazardous, this SDS contains valuable information critical to the safe handling and proper use of the product for industrial workplace conditions as well as unusual and unintended exposures such as large spills. This SDS should be retained and available for employees and other users of this product. For specific intended-use guidance, please refer to the information provided on the package or instruction sheet.	
1.3 Deta	ails of the supplier of the s	saf	ety data sheet	
Co	mpany	:	GOJO Industries-Europe Ltd. Units 5 & 6, Stratus Park MK10 0DE Brinklow, Milton Keynes	
Te	lephone	:	+44(0) 1908588444	
Te	lefax	:	+44(0) 1908588445	

E-mail address of person	: info@gojo.co.uk
responsible for the SDS	

### 1.4 Emergency telephone number

+44(0) 08445605135

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)		
Flammable liquids, Category 3	H226: Flammable liquid and vapour.	
Eye irritation, Category 2	H319: Causes serious eye irritation.	



Versio 1.3	n Revision Date: 11.02.2015		SDS Number: 3157-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014
	lassification (67/548/EEC,	199	•	
FI	ammable		R10: F	lammable.
Irr	ritant		R36: Irritating to eyes.	
2.2 La	bel elements			
La	abelling (REGULATION (E	C) I	No 1272/2008)	
H	azard pictograms	:	$\wedge$	
			< M > < !	
			V V	
Si	ignal word	:	Warning	
Ha	azard statements	:	H226	Flammable liquid and vapour.
			H319	Causes serious eye irritation.
Pi	recautionary statements	:	Prevention:	
			P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
			P233	Keep container tightly closed.
			P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
			Response:	
			P303 + P361 + P3	53 IF ON SKIN (or hair): Take off immedi- ately all contaminated clothing. Rinse skin with water/shower.
			P337 + P313	If eye irritation persists: Get medical advice/ attention.

### 2.3 Other hazards

Vapours may form explosive mixture with air.

### **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

#### Hazardous components

Chemical Name	CAS-No.	Classification	Classification	Concentration
	EC-No.	(67/548/EEC)	(REGULATION	(%)
	Registration		(EC) No	
	number		1272/2008)	
Ethanol	64-17-5	F; R11	Flam. Liq. 2; H225	>= 50 - < 70
	200-578-6	Xi; R36	Eye Irrit. 2; H319	
Propan-2-ol	67-63-0	F; R11	Flam. Liq. 2; H225	>= 3 - < 10
	200-661-7	Xi; R36	Eye Irrit. 2; H319	
		R67	STOT SE 3; H336	



Version	Revision Date:	MSDS Number:	Date of last issue: 14.01.2015
1.3	11.02.2015	33157-00004	Date of first issue: 02.12.2014

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

4.1 Description of first aid meas	sures			
General advice	<ul> <li>In the case of accident or if you feel unwell, seek medical advice immediately.</li> <li>When symptoms persist or in all cases of doubt seek medical advice.</li> </ul>			
Protection of first-aiders	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.			
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.			
In case of skin contact	: Wash with water and soap as a precaution. Get medical attention if symptoms occur.			
In case of eye contact	<ul> <li>In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.</li> <li>If easy to do, remove contact lens, if worn.</li> <li>Get medical attention.</li> </ul>			
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.			
4.2 Most important symptoms and effects, both acute and delayed				
Risks	: Causes serious eye irritation.			
4.3 Indication of any immediate	medical attention and special treatment needed			

Treatment : Treat symptomatically and supportively.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	:	Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet



Version 1.3	Revision Date: 11.02.2015	MSDS Number: 33157-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014					
5.2 Spe	5.2 Special hazards arising from the substance or mixture							
Specific hazards during fire- fighting		fire. Flash back po Vapours may≐	solid water stream as it may scatter and spread ssible over considerable distance. form explosive mixtures with air. ombustion products may be a hazard to health.					
Ha: uct	cardous combustion prod-	: Carbon oxides Silicon oxides						
5.3 Adv	ce for firefighters							
	ecial protective equipment firefighters		fire, wear self-contained breathing apparatus. protective equipment.					
Spe ods	ecific extinguishing meth-	cumstances a Use water spra	ning measures that are appropriate to local cir- nd the surrounding environment. ay to cool unopened containers. maged containers from fire area if it is safe to do					

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	<ul> <li>Remove all sources of ignition.</li> <li>Use personal protective equipment.</li> <li>Follow safe handling advice and personal protective equipment recommendations.</li> </ul>
6.2 Environmental precautions	
Environmental precautions	<ul> <li>Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers).</li> <li>Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages</li> </ul>

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	<ul> <li>Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet.</li> <li>For large spills, provide dyking or other appropriate contain- ment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-</li> </ul>
	bent.

cannot be contained.



Version	Revision Date:	MSDS Number:	Date of last issue: 14.01.2015
1.3	11.02.2015	33157-00004	Date of first issue: 02.12.2014
		posal of this ma employed in the mine which reg Sections 13 and	al regulations may apply to releases and dis- iterial, as well as those materials and items e cleanup of releases. You will need to deter- ulations are applicable. d 15 of this SDS provide information regarding national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

# **SECTION 7: Handling and storage**

7.1 Precautions for safe handling	
Technical measures :	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation :	Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.
Advice on safe handling :	Avoid inhalation of vapour or mist. Do not swallow. Do not get in eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Non-sparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Hygiene measures :	Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.
7.2 Conditions for safe storage, incl	luding any incompatibilities
Requirements for storage : areas and containers	Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
Advice on common storage :	Do not store with the following product types: Strong oxidizing agents Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures



Version 1.3	Revision Date: 11.02.2015	MSDS Number: 33157-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014
		Substances and flammable gases Explosives Gases	mixtures, which in contact with water, emit s
7.3 Specif	ic end use(s)		
Speci	fic use(s)	: No data availabl	e
		No data availabl	e

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
Ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m3	GB EH40	
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used				
Propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m3	GB EH40	
		STEL	500 ppm 1,250 mg/m3	GB EH40	
Glycerine	56-81-5	TWA (Mist)	10 mg/m3	GB EH40	
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used				

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Ethanol

· End Lise: Workers

- 2	End Use: Workers
	Exposure routes: Inhalation
	Potential health effects: Acute local effects
	Value: 1900 mg/m3
	End Use: Workers
	Exposure routes: Skin contact
	Potential health effects: Long-term systemic effects
	Value: 343 mg/kg bw/day
	End Use: Workers
	Exposure routes: Inhalation
	Potential health effects: Long-term systemic effects
	Value: 950 mg/m3
	End Use: Consumers
	Exposure routes: Inhalation
	Potential health effects: Acute local effects
	Value: 950 mg/m3
	End Use: Consumers
	Exposure routes: Skin contact
	Potential health effects: Long-term systemic effects
	Value: 206 mg/kg bw/day



Version 1.3	Revision Date: 11.02.2015	MSDS Number: 33157-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014
		End Use: Co	nsumers
			utes: Inhalation
			alth effects: Long-term systemic effects
		Value: 114 r	
		End Use: Co	
		Exposure ro	utes: Ingestion
			alth effects: Long-term systemic effects
_		Value: 87 m	
Propa	n-2-ol	: End Use: Wo	
		•	utes: Inhalation
			alth effects: Long-term systemic effects
		Value: 500 r End Use: Wo	
			utes: Skin contact
			alth effects: Long-term systemic effects
			ng/kg bw/day
		End Use: Co	
		Exposure ro	utes: Inhalation
		Potential hea	alth effects: Long-term systemic effects
		Value: 89 m	-
		End Use: Co	
			utes: Skin contact
			alth effects: Long-term systemic effects
		End Use: Co	ng/kg bw/day
			utes: Ingestion
			alth effects: Long-term systemic effects
		Value: 26 m	
Glyce	rine	: End Use: Wo	
2		Exposure ro	utes: Inhalation
		Potential hea	alth effects: Long-term local effects
		Value: 56 m	5
		End Use: Co	
			utes: Ingestion
			alth effects: Long-term systemic effects
		End Use: Co	ng/kg bw/day
			utes: Inhalation
			alth effects: Long-term local effects
		Value: 33 m	
Predic	cted No Effect Conce		cording to Regulation (EC) No. 1907/2006:
Ethan	ol	: Fresh water	
		Value: 0.96	mg/l
		Marine wate	
		Value: 0.79	-
		Intermittent u	
		Value: 2.75	
		Sewage trea	
		Value: 580 r	
		Fresh water Value: 3.6 n	
		Marine sedin	



Version 1.3	Revision Date: 11.02.2015	MSDS Number: 33157-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014	
Propan-2-ol		Value: 2.9 mg/kg Soil Value: 0.63 mg/kg Oral Value: 720 mg/kg : Fresh water Value: 140.9 mg/l Marine water Value: 140.9 mg/l Intermittent use/release Value: 140.9 mg/l Sewage treatment plant		
Glycerine		Sewage treatin Value: 2251 n Fresh water se Value: 552 m Value: 552 m Value: 552 m Value: 552 m Value: 552 m Value: 28 m Value: 28 m Value: 160 m Fresh water Value: 0.885 n Marine water Value: 0.0885 Intermittent us Value: 0.0885 m Sewage treatin Value: 1000 n Fresh water se Value: 3.3 m Marine sedime Value: 0.33 m Soil Value: 0.141 n	ng/l ediment g/kg ent g/kg mg/l g/kg mg/l se/release ng/l nent plant ng/l ediment g/kg ent ng/kg	
8.2 Expos	sure controls			
Engir	neering measures			

### **Engineering measures**

Minimize workplace exposure concentrations. Use only in an area equipped with explosion proof exhaust ventilation. Use with local exhaust ventilation.

Personal protective equipment			
Eye protection	ear the following afety goggles	g personal protective equipment:	
Hand protection Material	npervious gloves ame retardant g		
Remarks		protect hands against chemicals depending on and quantity of the hazardous sub-	



Version 1.3	Revision Date: 11.02.2015	MSDS Number: 33157-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014
		determined for the applications, we chemicals of the	cific to place of work. Breakthrough time is not he product. Change gloves often! For special recommend clarifying the resistance to a aforementioned protective gloves with the arer. Wash hands before breaks and at the
Skin and body protection		sistance data an tial. Wear the followi Flame retardant Skin contact mu	ate protective clothing based on chemical re- ad an assessment of the local exposure poten- ng personal protective equipment: antistatic protective clothing. st be avoided by using impervious protective aprons, boots, etc).
Respiratory protection		tilation is provide	protection unless adequate local exhaust ven- ed or exposure assessment demonstrates that <i>v</i> ithin recommended exposure guidelines.
Filter type		: Combined partic	culates and organic vapour type (A-P)

# **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

: liquid
: clear, Colorless to pale yellow
: alcohol-like
: No data available
: 6-9
: No data available
: No data available
: 23.6 °C
: No data available
: Not applicable
: No data available
: No data available
: No data available



Versi 1.3	on	Revision Date: 11.02.2015	-	DS Number: 57-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014	
F	Relative vapour density		:	No data available	•	
[	Density	,	:	: 0.88 g/cm3		
ç	Solubility(ies) Water solubility		:	soluble		
•	Partition coefficient: n- octanol/water		:	Not applicable		
ļ	Auto-ignition temperature		:	No data available	)	
Γ	Decomposition temperature		:	The substance of	r mixture is not classified self-reactive.	
١	Viscosity Viscosity, kinematic		:	10 - 20 mm2/s (2	0 °C)	
E	Explosive properties		:	Not explosive		
(	Oxidizing properties		:	The substance of	mixture is not classified as oxidizing.	
920	ther in	formation				

9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	: Flammable liquid and vapour.
	Vapours may form explosive mixture with air.
	Can react with strong oxidizing agents.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### **10.6 Hazardous decomposition products**

No hazardous decomposition products are known.



Version	Revision Date:	MSDS Number:	Date of last issue: 14.01.2015
1.3	11.02.2015	33157-00004	Date of first issue: 02.12.2014

### **SECTION 11: Toxicological information**

<b>11.1 Information on toxicological</b> Information on likely routes of exposure	
<b>Acute toxicity</b> Not classified based on availal	ble information.
Components:	
Ethanol: Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 124.7 mg/l Exposure time: 4 h Test atmosphere: vapour
Propan-2-ol:	
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 72.6 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	: LD50 (Rat): > 5,000 mg/kg
Skin corrosion/irritation Not classified based on availal	ble information

Not classified based on available information.

#### Product:

Result: No skin irritation

#### **Components:**

Ethanol: Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation

### Propan-2-ol:

Species: Rabbit Result: No skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.

**Components:** Ethanol:



Version	Revision Date:	MSDS Number:
1.3	11.02.2015	33157-00004

Date of last issue: 14.01.2015 Date of first issue: 02.12.2014

Species: Rabbit Method: OECD Test Guideline 405 Result: Irritation to eyes, reversing within 21 days

### Propan-2-ol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days

### Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

#### Product:

Assessment: Does not cause skin sensitisation.

#### **Components:**

#### Ethanol:

Test Type: Local lymph node assay (LLNA) Exposure routes: Skin contact Species: Mouse Result: negative

### Propan-2-ol:

Test Type: Buehler Test Exposure routes: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: negative

### Germ cell mutagenicity

Not classified based on available information.

### **Components:**

Ethanol: Genotoxicity in vitro :	Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo :	Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: Ingestion Result: negative
Propan-2-ol:	
•	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo :	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative



Version	Revision Date:	MSDS Number:	Date of last issue: 14.01.2015
1.3	11.02.2015	33157-00004	Date of first issue: 02.12.2014

#### Carcinogenicity

Not classified based on available information.

### **Components:**

Propan-2-ol: Species: Rat Application Route: inhalation (vapour) Exposure time: 104 weeks Method: OECD Test Guideline 451 **Result:** negative

#### **Reproductive toxicity**

Not classified based on available information.

#### Components: Ethanol: Effects on fertility : Test Type: Two-generation reproduction toxicity study Species: Mouse **Application Route: Ingestion** Method: OECD Test Guideline 416 **Result:** negative Propan-2-ol: Effects on fertility : Test Type: Two-generation reproduction toxicity study Species: Rat **Application Route: Ingestion** Result: negative Effects on foetal develop-Test Type: Embryo-foetal development Species: Rat ment **Application Route: Ingestion Result: negative**

### STOT - single exposure

Not classified based on available information.

### Components:

Propan-2-ol: Assessment: May cause drowsiness or dizziness.

#### STOT - repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### **Components:**

Ethanol: Species: Rat NOAEL: 2,400 mg/kg **Application Route: Ingestion** 



Version Revision Date: 1.3 11.02.2015

MSDS Number: 33157-00004

Date of last issue: 14.01.2015 Date of first issue: 02.12.2014

Exposure time: 2 y

### Propan-2-ol:

Species: Rat NOAEL: 5000 ppm Application Route: inhalation (vapour) Exposure time: 104 w Method: OECD Test Guideline 413

### Aspiration toxicity

Not classified based on available information.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

<u>Components:</u> Ethanol:				
Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h			
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h			
Toxicity to algae	<ul> <li>EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l</li> <li>Exposure time: 72 h</li> <li>Method: OECD Test Guideline 201</li> </ul>			
Toxicity to bacteria	: EC50 (Photobacterium phosphoreum): 32.1 mg/l Exposure time: 0.25 h			
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	: NOEC: 9.6 mg/l Exposure time: 9 d Species: Daphnia magna (Water flea)			
Propan-2-ol:				
Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l Exposure time: 96 h			
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h			
Toxicity to algae	<ul> <li>ErC50 (Scenedesmus quadricauda (Green algae)): &gt; 1,800 mg/l</li> <li>Exposure time: 8 d</li> </ul>			
Toxicity to bacteria	: EC50 (Pseudomonas putida): > 1,050 mg/l Exposure time: 16 h			



Version 1.3	Revision Date: 11.02.2015	MSDS Number: 33157-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014		
12.2 Pers	istence and degradab	ility			
Etha	Components:         Ethanol:         Biodegradability       : Result: Readily biodegradable Biodegradation: 84 % Exposure time: 20 d				
Prop	an-2-ol:		. 20 4		
-	egradability	: Result: rapidly	/ degradable		
12.3 Bioa	ccumulative potential				
Etha Partit octar Prop	ponents: nol: tion coefficient: n- nol/water pan-2-ol: tion coefficient: n-	: log Pow: -0.3			
	nol/water	. log i ow. o.oo			
	<b>ility in soil</b> ata available				
	ults of PBT and vPvB a elevant	assessment			
	er adverse effects ata available				
SECTIO	N 13: Disposal consi	derations			
13.1 Was	te treatment methods				
Prod	uct	According to t are not produ	accordance with local regulations. he European Waste Catalogue, Waste Coo ct specific, but application specific.		

	discussion with the waste disposal authorities.
Contaminated packaging	<ul> <li>Dispose of as unused product.</li> <li>Empty containers should be taken to an approved waste han- dling site for recycling or disposal.</li> <li>Do not burn, or use a cutting torch on, the empty drum.</li> </ul>

Waste codes should be assigned by the user, preferably in

# **SECTION 14: Transport information**

### 14.1 UN number



Version 1.3	Revision Date: 11.02.2015		SDS Number: 157-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014
ADN			UN 1987	
ADR			UN 1987	
RID			UN 1987	
IMD	2		UN 1987	
IATA			UN 1987	
	oroper shipping name	•	011 1907	
ADN		:	ALCOHOLS, N.O (Ethanol, Propan-	
ADR		:	ALCOHOLS, N.O (Ethanol, Propan-	.S.
RID		:	ALCOHOLS, N.O (Ethanol, Propan-	
IMDO	G	:	ALCOHOLS, N.O (Ethanol, Propan-	
ΙΑΤΑ	<b>N</b>	:	Alcohols, n.o.s. (Ethanol, Propan-	2-ol)
14.3 Tran	sport hazard class(es)			
ADN		:	3	
ADR		:	3	
RID		:	3	
IMDO	G	:	3	
ΙΑΤΑ	۱.	:	3	
14.4 Pack	king group			
Class	ing group sification Code ard Identification Number	:	III F1 30 3	
Class Haza Labe	ing group sification Code ard Identification Number	:	III F1 30 3 (D/E)	
Class			III F1 30 3	
	-			



major-

# PURELL® Skin Nourishing Foam Hand Sanitiser

Version 1.3	Revision Date: 11.02.2015	MSDS Number: 33157-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014	
Lab	cking group bels S Code	: III : 3 : F-E, S-D		
airc Pac	A cking instruction (cargo craft) cking instruction (passen- aircraft)	: 366 : 355		
	cking instruction (LQ) cking group pels	: Y344 : III : Flammable Liqu	iids	
	vironmental hazards			
<b>AD</b> Env	<b>N</b> <i>v</i> ironmentally hazardous	: no		
<b>AD</b> Env	<b>R</b> /ironmentally hazardous	: no		
<b>RID</b> Env	<b>)</b> <i>v</i> ironmentally hazardous	: no		
<b>IMI</b> Ma	<b>DG</b> rine pollutant	: no		
	ecial precautions for use applicable	r		
	n <b>sport in bulk accordin</b> g marks		RPOL 73/78 and the IBC Code or product as supplied.	

# **SECTION 15: Regulatory information**

6

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

•		
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EC) No 850/2004 on persistent organic pol- lutants	:	Not applicable
Seveso II - Directive 2003/105/EC amending Council Direction accident hazards involving dangerous substances		e 96/82/EC on the control of
		Quantity 1 Quar

Qua	ntity 1 Quantity 2
mmable. 5,0	000 t 50,000 t



Version 1.3	Revision Date: 11.02.2015	MSDS Number: 33157-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014						
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS 5,000 t 50,000 t									
34		Petroleum produ gasolines and na (b) kerosenes (in fuels), (c) gas oil ing diesel fuels, I heating oils and blending streams heavy fuel oils (e tive fuels serving purposes and wi properties as reg flammability and mental hazards a products referred points (a) to (d)	aphthas, icluding jet s (includ- nome gas oil s),(d) alterna- the same th similar jards environ- as the	2,500 t	25,000 t				
Volat	Volatile organic compounds: Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 75 %								
The components of this product are reported in the following inventories: AICS : All ingredients listed or exempt.									
AICS		: All ingredients lis	ted or exemp	π.					

#### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)

### **15.2 Chemical Safety Assessment**

A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

<ul><li>Highly flammable.</li><li>Irritating to eyes.</li></ul>				
: Vapours may cause drowsiness and dizziness.				
Full text of H-Statements				
<ul><li>Highly flammable liquid and vapour.</li><li>Causes serious eye irritation.</li><li>May cause drowsiness or dizziness.</li></ul>				

### Full text of other abbreviations



Versi 1.3		Revision Date: 11.02.2015		SDS Number: 157-00004	Date of last issue: 14.01.2015 Date of first issue: 02.12.2014		
Eye Irrit. Flam. Liq. STOT SE GB EH40 GB EH40 / TWA GB EH40 / STEL		:	<ul> <li>Eye irritation</li> <li>Flammable liquids</li> <li>Specific target organ toxicity - single exposure</li> <li>UK. EH40 WEL - Workplace Exposure Limits</li> <li>Long-term exposure limit (8-hour TWA reference period)</li> <li>Short-term exposure limit (15-minute reference period)</li> </ul>				
Further information Sources of key data used to compile the Safety Data Sheet		:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN